

## FWSA.EX15004 Fixed Condensed Aerosol Extinguishing System Units

Page Bottom

## **Fixed Condensed Aerosol Extinguishing System Units**

See General Information for Fixed Condensed Aerosol Extinguishing System Units

FIREAWAY INC 5852 BAKER RD MINNETONKA, MN 55345 USA

> Description Part No. Aerosol-generating extinguishing system unit 15100 Stat-X condensed aerosol generator, Model 30 E Stat-X condensed aerosol generator, Model 60 E 15110 Stat-X condensed aerosol generator, Model 60 E 15111 Stat-X condensed aerosol generator, Model 100 E 15120 15130 Stat-X condensed aerosol generator, Model 250 E Stat-X condensed aerosol generator, Model 500 E 15140 Stat-X condensed aerosol generator, Model 1000 E 15150 Stat-X condensed aerosol generator, Model 1500 E 15160 Stat-X condensed aerosol generator, Model 2500 E 15170 Aero-K condensed aerosol generator, Model G 30 11700 Aero-K condensed aerosol generator, Model G 60 11705 Aero-K condensed aerosol generator, Model G 100 11740 Aero-K condensed aerosol generator, Model G 250 11710 Aero-K condensed aerosol generator, Model G 500 11690 Aero-K condensed aerosol generator, Model G 1000 11770 11800 Aero-K condensed aerosol generator, Model G 1500 Aero-K condensed aerosol generator, Model G 2500 11850 18001 Mounting bracket, for Models G 30, G 60, 30 E and 60 E Mounting bracket, for Models G 100 and 100 E 18005 Mounting bracket, for Models G 250, G 500, 250 E and 500 E 18010 Mounting bracket, for Models G 1000, G 1500, G 2500, 1000 E, 1500 E and 2500 E 18015 Stat-X Design, Installation, Operation and Maintenance Manual, dated 2011-11 19000 19001 Stat-X Owner's Manual, dated 2011-11 Aero-K Design, Installation, Operation and Maintenance Manual, dated 2009-10 19002 19003 Aero-K Owner's Manual, dated 2009-10

For Class A surface burning and Class B and C category hazards; not for use in hazardous (classified) locations. Temperature range -40 to 54°C.

Last Updated on 2012-03-07

Questions?

Print this page

Notice of Disclaimer

Page Top

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".

EX15004